

Drills / Tappers

Tappers

Easy to use throttle and reversing trigger combined with a universal tapping chuck provide a smooth tapping operation. Fuji Tappers are available in tapping capacities from 6mm to 13mm.



Model	Type	Tapping Capacity (Guidance)				Free Speed (min ⁻¹)		Type and Size of Spindle Taper #	Chuck Capacity	Overall Length		Weight		Max. Air Consumption		Air Hose Size	
		Steel		Aluminum		R	L			mm	in	kg	lb	m ³ /min	ft ³ /min	mm	in
		mm	in	mm	in												
FT-6P-1	-	6	1/4	8	5/16	1,000	1,000	J.T.#1	8	236	9 19/64	1.8	4.0	0.50	17.7	9.5	3/8
FT-6BX-1	D	6	1/4	8	5/16	2,000	2,000	J.T.#1	6.5	205	8 7/64	1.3	2.9	0.56	19.8	8.0	5/16
FT-6BX-1	T	6	1/4	8	5/16	2,000	2,000	J.T.#1	8	240	9 29/64	1.3	2.9	0.56	19.8	8.0	5/16
FT-8PX-1	-	8	5/16	10	3/8	450	450	M.T.#1	9	232	9 9/64	2.0	4.4	0.50	17.7	9.5	3/8

*FT-6P-1, 6BX-1, 8PX-1: 1/4" Air Inlet Thread Size.

*TYPE: D...Drill Chuck, T...Tapping Chuck.



No.	Models	Type and Size of Spindle Taper #	Chuck Capacity
TCK-6	FT-6BX-1T	J.T.#1	8mm
TCK-8F	FT-8PX-1	M.T.#1	9mm



No.	Models	Type and Size of Spindle Taper #	Chuck Capacity
DCK-6.5J	FT-6BX-1(D Type)	J.T.#1	6.5mm
DCK-8J	FT-6P-1	J.T.#1	8mm