

Pulse Wrenches

SQUARE DRIVE TYPE



FPW-440SC~660SC



FPW-770SC-1

Model	Bolt Size	Recommended Torque Range			Free Speed	Square Drive Size		Overall Length (without socket)		Weight (without socket)		Air Consumption (at Load)		Air Hose Size	
		mm	N · m	kgf · m		ft · lb	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min	mm
Angle Head Models															
FPW-440SC-1	M4~M6	13~24	1.3~2.4	9.6~17.7	5,000	9.5	3/8	255	10 3/64	1.28	2.8	0.39	13.8	6.3	1/4
FPW-550SC-1	M6~M8	22~35	2.2~3.6	16.2~25.8	5,500	9.5	3/8	255	10 3/64	1.29	2.8	0.39	13.8	6.3	1/4
FPW-660SC-1	M6~M8	25~43	2.6~4.4	18.4~31.7	5,500	9.5	3/8	267	10 33/64	1.40	3.1	0.48	16.9	9.5	3/8
FPW-770SC-1	M8	33~50	3.4~5.1	24.3~36.9	6,300	9.5	3/8	271	10 43/64	1.70	3.7	0.50	17.7	9.5	3/8

*Air Inlet Thread Size: BSP or NPT 1/4".

Geared Pulse Wrenches

The Fuji Geared Pulse Wrenches Shut-Off type provides high power in combination with low noise and vibration through the Dual Chamber Air Motor & Gear-drive angle head.

The ergonomic design reduces the reaction forces experienced by the operator throughout the torque range.



FPW-770SCG-1

Model	Bolt Size	Recommended Torque Range			Free Speed	Socket Hex Size		Overall Length		Weight		Air Consumption (at Load)		Air Hose Size	
		mm	N · m	kgf · m		ft · lb	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min	mm
FPW-770SCG-1	M4~M6	21~30	2.1~3.1	15.5~22.1	7,000	12	15/32	343	13 33/64	2.0	4.4	0.50	17.7	9.5	3/8

*Air Inlet Thread Size: BSP or NPT 1/4".