

Die Grinders

EXTENDED TYPE MODELS



FG-26L-1BF



FG-3H-5F

Model	Collet Size		Max. Dia. (Mounted Wheel)		Free Speed min ⁻¹	Spindle Thread Size in	Power		Overall Length		Weight		Max. Air Consumption		Air Hose Size	
	mm	in	mm	in			kW	hp	mm	in	kg	lb	m ³ /min	ft ³ /min	mm	in
Locking Lever Handle Models																
FG-26L-1BF	6	1/4	25 x 13 x –	1 x 1/2 x –	24,000	5/16–24UNF	0.22	0.30	306	12 3/64	0.9	2.0	0.40	14.1	9.5	3/8
FG-3H-5F	6	1/4	45 x 13 x –	1 25/32 x 1/2 x –	14,600	3/8–24UNF	0.48	0.64	367	14 29/64	1.5	3.3	0.55	19.4	9.5	3/8

*Air Inlet Thread Size: BSP or NPT 1/4", FG-3H-5, 5F: BSP or NPT 3/8".

ANGLE TYPE MODELS



FA-2C-2BF, 3BF

Side Exhaust Type

Model	Collet Size		Max. Dia. (Mounted Wheel)		Free Speed min ⁻¹	Spindle Thread Size in	Power		Overall Length		Weight		Max. Air Consumption		Air Hose Size	
	mm	in	mm	in			kW	hp	mm	in	kg	lb	m ³ /min	ft ³ /min	mm	in
Locking Lever Handle Models																
FA-2C-2BF	6	1/4	38 x 13 x –	1 1/2 x 1/2 x –	15,000	3/8–24UNF(M)	0.26	0.34	188	7 13/32	0.7	1.5	0.40	14.1	9.5	3/8
FA-2C-3BF	6	1/4	38 x 13 x –	1 1/2 x 1/2 x –	15,000	W3/8–16(M)	0.26	0.34	188	7 13/32	0.7	1.5	0.40	14.1	9.5	3/8

*Air Inlet Thread Size: BSP or NPT 1/4".



FA-2CX-2BF, 3BF

Rear Exhaust Type

Model	Collet Size		Max. Dia. (Mounted Wheel)		Free Speed min ⁻¹	Spindle Thread Size in	Power		Overall Length		Weight		Max. Air Consumption		Air Hose Size	
	mm	in	mm	in			kW	hp	mm	in	kg	lb	m ³ /min	ft ³ /min	mm	in
Locking Lever Handle Models																
FA-2CX-2BF	6	1/4	38 x 13 x –	1 1/2 x 1/2 x –	15,000	3/8–24UNF(M)	0.26	0.34	226	8 57/64	1.0	2.2	0.40	14.1	9.5	3/8
FA-2CX-3BF	6	1/4	38 x 13 x –	1 1/2 x 1/2 x –	15,000	W3/8–16(M)	0.26	0.34	226	8 57/64	1.0	2.2	0.40	14.1	9.5	3/8

*Air Inlet Thread Size: BSP or NPT 1/4".